

FORM PTO-1390
(Rev. 1-98)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER JAB-1513

**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

10/018583

INTERNATIONAL APPLICATION NO.

INTERNATIONAL FILING DATE

PRIORITY DATE CLAIMED

PCT/EP00/06245

July 3, 2000

July 3, 1999

TITLE OF INVENTION

APPARATUS FOR TRANSPORTING CARRIERS TO A PROCESSING STATION AND
METHOD OF OPERATING THE SAME


APPLICANT(S) FOR DO/EO/US : Roger Francois Gabrielle Armand Nuyens

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371 (c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A FIRST preliminary amendment.
☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☐ Other items or information:

U.S. APPLICATION NO. (if known, see 37 CFR 1.53) 10/018583		INTERNATIONAL APPLICATION NO PCT/EP00/06245		ATTORNEY'S DOCKET NUMBER JAB-1513	
17. <input type="checkbox"/> The following fees are submitted: BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)): Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO..... \$1040.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO.....\$890.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.455(a)(2)) paid to USPTO..... \$740.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4)..... \$750.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4)..... \$100.00 ENTER APPROPRIATE BASIC FEE AMOUNT =				CALCULATIONS PTO USE ONLY	
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				\$	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	14 - 20 =	0	x \$18.00	\$000.00	
Independent claims	3 - 20 =	0	x \$84.00	\$000.00	
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$280.00	\$000.00	
TOTAL OF ABOVE CALCULATIONS =				\$930.00	
Reduction of 1/2 for filing by small entity, if applicable. A Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28).				\$	
SUBTOTAL =				\$930.00	
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$	
TOTAL NATIONAL FEE =				\$930.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +				\$ 40.00	
TOTAL FEES ENCLOSED =				\$970.00	
				Amount to be refunded:	\$
				charged:	\$
a. <input type="checkbox"/> A check in the amount of \$ _____ to cover the above fees is enclosed. b. <input checked="" type="checkbox"/> Please charge my Deposit Account No. <u>10-0750/JAB-1513/ECC</u> in the amount of \$970.00 to cover the above fees. A duplicate copy of this sheet is enclosed. c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <u>10-0750/JAB-1513/ECC</u> . A duplicate copy of this sheet is enclosed.					
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b)) must be filed and granted to restore the application to pending status.					
SEND ALL CORRESPONDENCE TO: Philip S. Johnson, Esq. Johnson & Johnson One Johnson & Johnson Plaza New Brunswick, NJ 08933-7003 USA					
 Signature Ellen Ciambrone Coletti Reg. No. 34,140 Attorney for Applicants					

10/018583

JG18 Rec'd PCT/EP 17 DEC 2001

Docket No. JAB-1513

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants : Roger F.G.A. Nuyens
Serial No. :
Filed :
Title : APPARATUS FOR TRANSPORTING CARRIERS TO A PROCESSING
STATION AND METHOD OF OPERATING THE SAME

Art Unit :
Examiner :

Honorable Commissioner of Patents
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Dear Sir:

Prior to examination, please amend the captioned application as follows:

In the Specification:

Please add the following paragraph at page 1, between the Title and line 4:

-- Cross Reference to Related Applications

This application is the national stage filing of PCT Application No.
PCT/EP00/06245 filed July 3, 2000, which application claims priority from EPO application
No. 99202173.3, filed July 3, 1999. --

In the Claims:

Please amend the claims as follows:

3. The transporter according to claim 1, wherein the singulator is adapted to move a received carrier incrementally upwards or downwards at the intermediate position independent of any movement of the carriers in the first and/or second magazines.

4. The transporter according to claim 1 wherein the singulator comprises a release mechanism and a conveyor, the release mechanism releasing carriers from the first magazine one-at-a-time to the conveyor.

5. The transporter according to claim 1, wherein the conveyor of the singulator comprises a pair of opposed belts, the belts having external protuberances or ledges and the belts being arranged vertically, so that the external ledges from the two belts define horizontally-oriented shelves which are capable of holding a received carrier in a substantially horizontal orientation.

6. The transporter according to claim 1, further comprising a processing tool movable horizontally to a location above and/or below the carrier when the carrier is at the intermediate position in the singulator.

9. The transporter according to claim 7, wherein the carriers are Petri dishes, multi-well plates or any other device containing biological specimens.

12. The method according to claim 10, further comprising the steps of:

moving a processing tool horizontally to a position above and/or below the carrier at the intermediate position; and

withdrawing the processing tool after carrying out processing.

13. The method according to claim 10, wherein the movement of the carrier to the intermediate position is independent of movements of the carriers in the input and output magazines.

14. The method according to claim 12, wherein the processing tool is an optical receiver.

REMARKS/ARGUMENTS

Claims 1-14 remain in this application. Claims 2-6, 9, and 12-14 have been amended.

Consideration of the captioned application in view of the foregoing amendments is requested.

The specification has been amended to refer to the priority application.


Accordingly, the claims pending and under consideration are claims 1-14.

Enclosed herewith are copies of the International Search Report, the references cited in the search report and a completed form PTO-1449.

Early favorable action on the merits is respectfully requested.

Attached hereto is a marked-up version of the changes made to the specification and claims by the current amendment. The attached page(s) is/are captioned "Version with markings to show changes made".

Respectfully submitted,

By: 
Ellen Ciambone Coletti
Reg. No. 34,140

Johnson & Johnson
One Johnson & Johnson Plaza
New Brunswick, NJ 08933-7003
(732) 524-2359
Dated: December 13, 2001

VERSION WITH MARKINGS TO SHOW CHANGES MADE

In the Specification:

Please add the following paragraph at page 1, between the Title and line 4:

-- Cross Reference to Related Applications

This application is the national stage filing of PCT Application No. PCT/EP00/06245 filed July 3, 2000, which application claims priority from EPO application No. 99202173.3, filed July 3, 1999. --

In the Claims:

Please amend the claims as follows:

3. The transporter according to claim 1 [or 2,] wherein the singulator is adapted to move a received carrier incrementally upwards or downwards at the intermediate position independent of any movement of the carriers in the first and/or second magazines.

4. The transporter according to [any previous] claim 1 wherein the singulator comprises a release mechanism and a conveyor, the release mechanism releasing carriers from the first magazine one-at-a-time to the conveyor.

5. The transporter according to [any of the previous claims] claim 1 wherein the conveyor of the singulator comprises a pair of opposed belts, the belts having external protuberances or ledges and the belts being arranged vertically, so that the external ledges from the two belts define horizontally-oriented shelves which are capable of holding a received carrier in a substantially horizontal orientation.

6. The transporter according to [any previous] claim 1, further comprising a processing tool movable horizontally to a location above and/or below the carrier when the carrier is at the intermediate position in the singulator.

9. The transporter according to [any previous] claim 7, wherein the carriers are Petri dishes, multi-well plates or any other device containing biological specimens.

12. The method according to claim 10 [or 11], further comprising the steps of:
moving a processing tool horizontally to a position above and/or below the carrier at the intermediate position; and
withdrawing the processing tool after carrying out processing.

13. The method according to [any of claims] claim 10 [to 12], wherein the movement of the carrier to the intermediate position is independent of movements of the carriers in the input and output magazines.

14. The method according to claim 12 [or 13], wherein the processing tool is an optical receiver.

3/p.12

1

APPARATUS FOR TRANSPORTING CARRIERS TO A PROCESSING
STATION AND METHOD OF OPERATING THE SAME

The present invention relates to handling of objects, particularly objects to be scanned
5 optically or viewed as for instance microscope slides, specimen carriers, trays or Petri
dishes. In particular, the present invention relates to an apparatus and method for
transporting carriers, such as microscope slides or trays to a processing position..

TECHNICAL BACKGROUND OF THE INVENTION

10 Devices for conveying specimens particularly for clinical laboratories are
known from DE-U-297 12 535, WO 97/39348, WO 93/06516. However, most of these
devices need to grasp the specimen, or push the specimen sideways out of a vertical
magazine to a viewing position or need to move them in some other way to a viewing
or processing position. It is often inconvenient grasp or push a delicate specimen
15 holder such as a microscope slide, either because the slide is fragile, or because the
specimen, or the indicia imprinted on the slide, can easily be abraded and thus
obliterated. In addition, the known devices require a separate mechanism for
autofocusing onto the specimen to be viewed. For example, autofocusing mechanisms
are known from WO 96/01438, US 3,721,759, WO 96/10196, US 5,790,692, US
20 5,790,710. These require a stage for moving the specimen in at least two dimensions
and often in three. This stage is in addition to the vertical delivery systems described
above. Each specimen must be conveyed to a first position with one mechanism,
transferred to a viewing position with another mechanism and then autofocused using
yet another mechanism. This makes the combination expensive, bulky and complicated.

25 It is an object of the present invention to provide a compact system and method
for delivery of specimens, particularly those to be viewed optically, to a processing or
viewing position.

It is a further object of the present invention to provide an apparatus and method
for obtaining an autofocus position for an optical instrument in a short time.

30 It is a further object of the present invention to provide an apparatus and method
for obtaining an autofocus position for an optical instrument which is simple, compact
and less expensive than known apparatus and methods.

SUMMARY OF THE INVENTION

One aspect of the present invention is to integrate components of laboratory equipment, so that the components can cooperate as a compact unified, fully automated system. In one embodiment, the invention provides a transporter for transporting
 5 specimen carriers to a processing station, comprising a first vertical input magazine of carriers, a second vertical output magazine of carriers, and a singulator located between the first and second magazines. The first and second magazines may be located one above the other. Preferably, the first and second magazines and the singulator are vertically aligned so that a carrier follows a straight vertical path. This provides a
 10 compact arrangement which takes up the minimum of floor space in the laboratory. The singulator receives carriers one-at-a-time from the input magazine and moves them vertically to a processing position. After processing, the singulator then delivers each carrier to an output location where it is transferred to the output magazine. The singulator may move a carrier upwards or downwards at the processing position
 15 independent of any movement of the carriers in the input and/or output magazines. Hence, the singulator can move a carrier to a predetermined distance from either the input magazine and/or the output magazine and can adjust this position in both directions. In particular, the singulator is adapted to move a carrier very accurately and finely about the processing position, e.g. to allow autofocusing. The singulator may be
 20 described as micro-positioning, micro-stepping, micro-incrementing or micro-indexing. The drives for the input and output magazine are preferably simple gravity drives but the present invention is not limited thereto. The drive for the singulator is preferably a stepping motor or DC servo-motor. The processing position is at a location within the movement of the singulator.

25 The present invention may include in one embodiment a singulator comprising a release mechanism and a conveyor. The conveyor may comprise a pair of opposed belts, the belts having external protuberances or ledges. The belts are arranged vertically, so that the external ledges from the two belts define horizontally-oriented shelves which are capable of holding specimens such as carriers, slides, or other
 30 objects, in a generally horizontal orientation. The movement of the belts is preferably synchronized such that the specimens may be conveyed vertically up and down in their horizontal orientation while the belts move. The singulator is preferably adapted so that it not only transports the specimen carrier or slide to a viewing position but also

provides the necessary fine vertical movements for autofocusing at the viewing position. The singulator of the present invention may also be used to transport specimens to a processing position which does not involve optical scanning but may involve other processes.

5 For this purpose, the transporter in accordance with the present invention may include a processing tool which may be moved horizontally to a location above and/or below the carrier at the processing position in the singulator. Further, it is preferred if the singulator spaces the selected carrier from the output and input magazines at the processing position to allow room for the processing tool to be introduced above and/or
10 below the selected carrier. The processing tool is preferably an optical receiver for capturing an image, e.g. a video image of the contents of the carrier. The processing tool may be any other suitable tool, e.g. a microscope or a fluorescent microscope.

The present invention includes a method of transporting specimen carriers to a processing position, comprising the steps of: providing a vertical input magazine and a
15 vertical output magazine of carriers; singling out a carrier from the input magazine and moving it vertically to the processing position which is located between the input and output magazines; and moving the carrier to an output location where it is transferred to the output magazine.

The step of moving the carrier to the processing position is preferably carried
20 out in such a way that there is no simultaneous movement of the carriers in the input and/or output magazines. As only one carrier is moved to the processing position at a time, the load on a drive motor is low. Further, it is preferred if the singling out and moving steps space the selected carrier from the output and input magazines to allow room for a processing tool to be introduced above and/or below the selected carrier
25 when the carrier is at the processing position. The present invention includes moving the processing tool horizontally to a position above and/or below the carrier at the processing position and withdrawing the processing tool after carrying out processing to allow the carriers to pass. The processing tool is preferably an optical receiver for capturing an image, e.g. a video image of the contents of the carrier. The processing
30 tool may be any other suitable tool, e.g. a microscope or a fluorescent microscope.

The dependent claims each define a separate and individual embodiment of the present invention. The present invention will now be described with reference to the following drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is schematic side-view representation of the transport apparatus according to an embodiment of the present invention.

5 Fig. 2 is a schematic top view of the apparatus of Fig. 1.

Figure 3 is a detail of the cam mechanism for allowing a single specimen to enter the singulator.

Fig. 4 is a side view of one type of a specimen carrier which may be used with the present invention.

10 Fig. 5 is a schematic cross-section of an optical receiver in accordance with the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATIVE EMBODIMENTS

The present invention will be described with respect to certain embodiments and 15 to certain schematic drawings but the present invention is not limited thereto but only by the claims.

Figs. 1 and 2 show schematically a side-view (with front plate 30 removed) and a top-view (with the input magazine 1 removed) of the transporter 100 in accordance with an embodiment of the present invention. Generally, the transporter 100 includes a 20 vertical input magazine 1 of specimen carriers 8, a singulator 3 and an output magazine 6 of carriers 8. Each carrier 8 may contain one or more wells 9 in which liquid samples, in particular, cell cultures and other biological specimens may be placed. The word carrier is meant to be interpreted in a wide sense and may include petri dishes, trays, multiwell trays, microscope slides or holders for microscope slides or any other similar 25 carrier, tray or specimen holder which can be stacked in an input stack and moved to a processing position. The singulator 3 receives a single carrier 8' from the input magazine 1 via cam-driven release means 2. The singulator 3 then conveys the substantially horizontal carrier 8' vertically to a processing position 40. Singulator 3 can move the carrier 8' both upwards and downwards. Due to the fact that the singulator 3 30 only has to move a single carrier 8, the power required for the drive for the singulator 3 is low. Also, due to the low load on this drive, high positional accuracy and fine control of movement can be obtained, e.g. by using a stepper motor or DC servo-motor drive.

As shown schematically in Figs. 1 and 2, a singulator 3 according to an

embodiment of the present invention includes a release mechanism 2 and a conveyor comprising four belts 16, 17 arranged in a generally vertical orientation. Each belt 16 runs on a pair of pulleys 25, 28. Each belt 17 runs on four pulleys 24, 26, 27, 29.

Pulleys 24, 29 are mechanically biased, e.g. sprung loaded, and movable to stretch belt 17 in such a way that the carrier 8 is pressed against a guide plate 14 in the processing position 40. Belts 16, 17 have a plurality of protuberances or ledges 15, located on the outer surface of each belt and projecting substantially perpendicularly to the longitudinal direction of each belt. The belts 16, 17 are preferably made of rubber or other elastomer, or a rubber-like or elastomeric material, in particular fibre reinforced rubber or elastomer or rubber impregnated or elastomer impregnated textile or of some other flexible but preferably not stretchable material. The present invention is not limited to rubber or rubber substitutes. The portions of belts 16, 17 facing each other are spaced apart and move parallel to each other. The inner distance between the belts 16, 17 is greater than the outer dimension of the carriers 8, so as to allow the carriers 8 to fit between the belts 16, 17. The distance between the protuberances 15 on the two belts 16, 17 is less than the outer dimension of the carriers 8, so that each carrier 8 can be carried by four protuberances 8, one from each of the four belts 16, 17.

The pulleys 25, 28 of belt 16 rotate in a direction opposite to that of the pulleys 24, 26, 27, 29 of belt 17. The protuberances 15 on two belts 16, 17 which face each other move in the same vertical direction. The rotation of the pair of pulleys 25, 28 is preferably synchronized with the rotation of the four pulleys 25, 26, 27, 29 so that a carrier 8 supported by the protuberances 15 remains in horizontal position during the movement. The carriers 8 may be moved either up or down by singulator 3, depending on the direction of rotation of the pulleys 24-29. Upper pulleys 27, 28 are each fixed to an axle 37, 38 respectively. Axles 37, 38 are journaled in two fixed, parallel spaced support plates 30. Axles 37, 38 are fixed at one end to pulleys 35, 36. Pulleys 35, 36 are driven by a further belt 11 which is driven by a motor 33 having a pulley 10 fixed to its output shaft. The belt 11 may be tensioned by a tensioning pulley 12 in a conventional way. Motor 33 is preferably a motor which can be driven accurately and in small increments, e.g. a stepping motor or a DC-servo-motor. Driving pulleys 35, 36 causes axles 37, 38 to rotate, hence driving pulleys 27, 28 and belts 16, 17. The backlash in the drive for belts 16, 17 should preferably be kept to a minimum by maintaining a constant positive tension in belts 16, 17 and/or to use a non-slip drive between the belts 16, 17

and the pulleys 24, 26, 27, 29, e.g. driving belts and passing profiled pulleys. In accordance with the present invention the backlash is preferably kept below 1 mm, more preferably 500 micron or less, and most preferably 300 micron or less. The backlash is preferably compensated for in the controller of the motor 33, e.g. on

5 changes of direction the motor is moved a set distance, more than specified in order to take up the backlash. The repeatability of a vertical position, i.e. the accuracy of the system is preferably better than 100 micron, more preferably 50 micron or less and most preferably 30 micron or less. 10 micron is typical. An aspect of the present invention is the provision of what may be described as a micro-incrementing, micro-

10 positioning or micro-stepping singulator. This means that the singulator can be incremented in small steps of the order of 10 microns or less in one direction. One use of the singulator in accordance with the present invention is to bring a specimen carrier to a processing position and then to use the singulator to microindex the carrier up and down, e.g. to find a focussing position of a microscope. Thus, in accordance with the

15 present invention, the singulator is not only a transporter for transporting a carrier from an input magazine to an output magazine, but also a singulator which can be halted at an intermediate position, moved accurately, if necessary, into a pre-determined vertical position and then can be incremented up and down about this position. All these movements can be carried out using the same motor and belt drive.

20 An operation of the transporter will now be described. A plurality of carriers 8 is first loaded into an input magazine 1. A weight 7 may be applied to the top of the magazine to provide a gravity drive therefor. Carriers 8 are prevented from entering the singulator 3 by a cam-driven release mechanism 2. Once allowed onto the conveyor 16, 17, each carrier 8 is carried and conveyed by belts 16, 17. A carrier 8 is supported

25 between protuberances 15 and is lowered to the processing position 40. By further movement of belts 16, 17 it is deposited into an output magazine 6.

To synchronize belts 16, 17 it is preferred if all of the pulleys 25, 26, 27, 28 have the same diameter, and are made to turn at the same rate. The pulleys 25-28 can be adjusted at the start so that the corresponding protuberances 15 on each belt

30 combination 16, 17 are aligned horizontally. Sensor devices may be provided (not shown) to check that opposite protuberances 15 carry carriers 8 in a horizontal position. If a carrier 8 is not sufficiently horizontal, an error may cause an alarm.

The release mechanism 2 is driven in synchronism with the conveyor belts 16,

17 so that only one carrier 8 is released from the input magazine 1 onto the conveyor belts 16, 17 at a time. Fig. 3 shows a detailed schematic representation of the cam 41 and the cam follower 45 of release mechanism 2. It is advantageous to drive the cam 41 with the same motor 33 as is used to drive axles 37, 38. By this means the required

5 synchronism between the cam 41 and the conveyor belts 16, 17 can be maintained. As shown in Fig. 2, the cam 41 is fixed to axle 38 and is located between the pulleys 28. Two release mechanisms 2 are provided opposite each other for holding and releasing carriers 8. As shown the release mechanisms 2 are placed on either side of a carrier 8 close to a pulley 27, 28 respectively. The present invention is not limited thereto. For

10 instance, the release mechanisms 2 may be placed across the dimension of the carrier 8 which is 90° to that shown in Fig. 2.

A release mechanism 2 may include one or more (two are shown) support members 47 which are rotatably journaled on an axle 48. The release mechanism 2 also includes a cam follower 45 which bears on a cam 41 having one or more V-shaped

15 notches 42. Each V-shaped notch 42 is bounded by sloping bearing surfaces 43, 44. Cam 41 may have a generally circular shape so that cam follower 45 remains at the same position as cam 41 rotates until a notch 42 is reached. As cam 41 rotates further cam follower 45 moves down the first sloping surface 43 and the support member 47 rotates about axle 48 making the gap between the ends of the support members 47

20 larger. This allows a carrier 8 to slide downwards past the ends of the support members 47. The position of the notch 42 is synchronized with the movement of belts 16, 17 so that a carrier 8' is lowered past the ends of support members 47 as protuberances 15 are at a suitable position to support this carrier 8'. As axle 38 continues to rotate the carrier 8' is lowered by movement of belts 16, 17. At the same time cam follower 45 rides up

25 the surface 44 thus bring the end of support member 47 back to the sides of the next carrier 8 in the input magazine 1. Preferably, the relative position of the two sloping walls 43, 44 of a notch 42 may be varied so that the distance therebetween changes. For a given radius of cam 41, increasing the distance between the two sloping walls 43, 44 increases the distance that the singulator 3 moves before the support member moves

30 back up and supports the next carrier 8. Thus, by varying the distance between the walls 43, 44, the singulator 3 can be adapted to carriers 8 of different depths.

Preferably, a carrier 8 has the side-view form shown in Fig. 4 and in particular it is preferred if the carriers 8 are suitable for stacking, e.g. with a smaller upper part 51

than lower part 52. The next carrier 8 in the stack forms a lip 53. Preferably, carriers 8 are designed so that the top of one carrier seals off against the bottom of the carrier above. This is advantageous when the carriers 8 contain liquids and evaporation of these liquids should be prevented or reduced. As support member 47 returns to its

5 initial position it engages with lip 53 of the next carrier 8 in the input magazine 1 and prevents this carrier from moving downwards any further at this time. The distance traveled by belts 16, 17 as cam 41 rotates from one notch 42 to the next is preferably equal to the travel of a carrier 8 from the top of the singulator to the bottom thereof, so that only one carrier 8 is present in the singulator 3 at any time. The present invention is

10 not limited thereto. For instance two carriers 8 may be present in the singulator 3 at any one time provided these carriers 8 are adequately spaced apart.

Release of a carrier 8 from the singulator 3 to the output magazine 6 occurs automatically as belts 16, 17 travel around pulleys 25, 26. At this point the corresponding protuberances 15 move apart and allow each carrier 8 to descend into the

15 output magazine 6. Output magazine 6 may include a plate 21 and flexible ropes 19 attached thereto. These ropes 19 run over the axles of the pulleys 25, 26 and are attached to flexible counter-weights 22 in housings 23. Movement of the ropes 19 may be enabled in one direction only by gravity and clamps 18 which press a rope 19 against the axle of the pulley 25 or 26 may prevent reverse motion. As the input

20 magazine 6 moves down with increasing numbers of carriers 8, a longer length of counter-weight 22 is lifted up. By adjusting the weight of the flexible counter-weight 22, the additional weight of a carrier 8 in the output magazine 6 is compensated by the additional length of flexible counter-weight 22.

The transporter 100 described above is particularly useful for the delivery of

25 carriers 8 to a optical viewing position 40 and for autofocus adjustments of the position of each carrier 8 at this position although the present invention is not limited only to optical viewing but includes additional or alternative operations such as laser cutting or trimming, addition of chemical compounds such as dies, solvents, reagents or similar, heating, cooling, drying, cutting etc. At the processing position 40 one or more tools 5

30 may be introduced horizontally from one or both sides of the carrier 8'. In addition tool or tools 5 may be introduced either above and/or below the carrier 8'. In particular, tool 5 may include an optical receiver 5A and a light source 5B arranged above and below the carrier 8' respectively. Optical receiver 5A and light source 5B may be attached to

an XY stage 4, which can move the tool 5 in a plane XY which is perpendicular to the movement direction of carrier 8' in the singulator 3 (the Z direction). Stage 4 may be driven in the orthogonal X and Y directions by motors 31, 32, e.g. stepping motors or DC-servo motors. In operation, the tool 5 may normally be kept retracted so that it does not interfere with the operation of the singulator 3 and carriers 8. Once a carrier 8 has reached the processing position 40, the tool 5A may be moved into the carrier region using the stage 4. The present invention is not limited to only one processing position 40 but may include several, whereby the contents of carrier 8 are processed sequentially at the processing positions.

A purpose of the singulator 3 is to single out each carrier 8 to be measured and to provide sufficient distance between the singled out carrier 8' and the next carrier (stored at the bottom of the input magazine 1) so that the tool 5 may be moved into the space above and/or below the carrier 8' at the processing position 40. Preferably, sufficient space is also allowed at the processing position 40 between the singled out carrier 8' and the previous carrier 8 (stored at the top of the output magazine 6). Preferably, there is a free, unobstructed space above at least a central portion of the singled out carrier 8' which extends up to the bottom of the next carrier 8. The provision of this space is accomplished while keeping the input and output magazines 1, 6 very compact as each carrier 8 rests on the next one in these magazines. This free space is greater than the spacing of the carriers 8 in the input magazine 1 and may also be greater than the spacing between the protrusions or ledges 15 of the singulator 13. A further aspect of the singulator 3 is to provide vertical movements, both up and down, of the carrier 8' without any influence on the output magazine 6 or the input magazine 1. This allows Z direction movement of the carrier 8' to provide focusing of the contents of carrier 8' in the optical receiver 5A when the carrier is at the processing position 40.

An embodiment of an optical receiver 5A and light source 5B in accordance with the present invention is shown in schematic cross-section in Fig. 5. The optical receiver 5A may include a prism 5, at its outer end remote from a camera 34 to deflect light traveling vertically from the specimen carrier 8 along tube 52 in the horizontal direction towards a camera 34. Within the tube 52 of the optical receiver 5A one or more suitable filters, lenses 53 or diaphragms 54 may be placed to direct the light from the carrier 8 to the camera 34. Camera 34 may be a video camera attached to suitable

equipment for recording the video image of the specimen carrier 8, e.g. a personal computer (PC) with a video frame grabber and suitable digital storage means, e.g. a hard disk. Light for illuminating a carrier 8 may be optionally directed onto the specimen carrier 8' from above using a light source 5B including a fiber bundle 39
 5 attached to the optical receiver 5A. Optical receiver 5A is preferably made telescopic so that its length can be adjusted to the focal length of the objective lens 53 used.

Light source 5B may also include a prism at its extreme end to direct light from along the fibre optic cable 39 to the specimen carrier 8. Further, one or more suitable diaphragms 56, condensers 57 or filters 58 may be placed between the prism 55 and the
 10 fibre optic cable 39 to direct light travelling along the fibre optic cable 39 to the prism and to control its projected spot size and colour.

Instead of being attached to an XY stage, the optical receiver 5A may be attached to an XYZ stage (not shown) so that focusing of the image received by the camera 34 may be accomplished by Z direction movements of the stage. However, it is
 15 preferred in accordance with the present invention if the Z direction movements are carried out by the singulator 3. The reason for this is that the optical receiver 5A and camera 34 are heavy and movements in particular acceleration of these parts can cause vibrations and shocks to the complete system which can disturb the focusing operations and slow these down as it is necessary to wait between each movement until vibrations
 20 have ceased in order to capture an image accurately. The carrier 8 and the conveyor belts 16, 17 are light and cause little mechanical disturbance thus allowing much more rapid focusing onto the contents of carrier 8. This accelerates automatic screening.

To improve focusing still further, a device 20 may be provided for clamping the carrier 8' at the focused position 40. Clamping device 20 (best shown in Fig. 1) may
 25 include two pulleys 24, 29 for engagement with the outer portion and inner portion of belt 17 respectively. Between the two pulleys 24, 29 is placed a small actuator which drives pulley 29 against the side of carrier 8' when suitably stimulated. The actuator may be a spring. By this means the carrier 8' is clamped between the pulley 29 and a fixed plate 14 in a steady position even when optical receiver 5A is moved sideways by
 30 stage 4, e.g. when moving from one field to another or from one well to another of the specimen carrier 8'. A position sensor 13 such as a microswitch may be used to indicate when the carrier 8 is at the processing position 40. The output of the sensor 13 may be used for activating the movement of tool 5 into the processing area.

The control of the various components of transporter 100 including the movements of stage 4, belts 16 and 17 and clamp 20 may be carried out using suitable 3-axis control devices, e.g. MultiControl 2000 supplied by Märzhauzer and a PC computer running suitable programmable software.

5 While the invention has been shown and described with reference to preferred embodiments, it will be understood by those skilled in the art that various changes or modifications in form and detail may be made without departing from the scope and spirit of this invention as defined in the attached claims. For example, the input magazine 1 has been described above and shown in the attached drawings as being
10 located above the output magazine but the present invention is not limited thereto. The input magazine may be placed below the output magazine with the singulator between the two. In this case the carriers in the input magazine are driven upwards and the singulator receives a carrier and conveys it upwards towards the processing position and the output magazine. This embodiment of the present invention requires motor
15 drives for the input and output magazines which is less preferred. Alternatively, in accordance with an embodiment of the present invention devices may be included for transporting the carrier 8 when it has arrived at the processing position 40 to a different processing area, e.g. by moving the carrier 8 horizontally out of the singulator 3 and optionally returning it to the singulator 3 after this processing.

20 The present invention has been described with reference to an input magazine and an output magazine of carriers but the present invention is not limited thereto. The carrier may be moved to the processing position and removed therefrom to some other place so that only the input magazine is generally required for the present invention. Alternatively, the carriers may no longer be required after processing at the processing
25 position and the carrier may simply be discharged from the bottom of the singulator. For instance, the carrier may simply fall from the bottom of the singulator into a bin.

CLAIMS

1. A transporter for transporting carriers to a processing station, comprising:
a first vertical input magazine of carriers, a second output magazine of carriers, the first
5 and second magazines being located one above the other in either order; and
a singulator located between the output of the first magazine and the input of the second
magazine, the singulator being adapted to receive one carrier at a time from the first
magazine and to move the carrier from the first magazine vertically to a position
intermediate the first and the second magazines and to halt the carrier at this position.
10
2. A transporter for transporting specimen carriers, comprising:
a first vertical input magazine of carriers, the carriers in the first magazine being spaced
at a carrier spacing distance; a singulator adapted to receive one carrier at a time from
the first magazine and to move a received carrier vertically from a first position at the
15 output of the first magazine to a second position at which a carrier may be discharged
from the singulator; wherein the singulator is adapted to move a received carrier and to
halt it at an intermediate position located between the first and second positions to
space the received carrier from the next carrier in the first input magazine by a distance
greater than the carrier spacing distance.
20
3. The transporter according to claim 1 or 2, wherein the singulator is adapted to move
a received carrier incrementally upwards or downwards at the intermediate position
independent of any movement of the carriers in the first and/or second magazines.
- 25 4. The transporter according to any previous claim wherein the singulator comprises a
release mechanism and a conveyor, the release mechanism releasing carriers from the
first magazine one-at-a-time to the conveyor.
5. The transporter according to any of the previous claims wherein the conveyor of the
30 singulator comprises a pair of opposed belts, the belts having external protuberances or
ledges and the belts being arranged vertically, so that the external ledges from the two
belts define horizontally-oriented shelves which are capable of holding a received
carrier in a substantially horizontal orientation.

6. The transporter according to any previous claim, further comprising a processing tool movable horizontally to a location above and/or below the carrier when the carrier is at the intermediate position in the singulator.

5

7. The transporter according to claim 6, wherein the processing tool is an optical receiver for capturing an image, in particular a video image of the contents of the carrier.

10

8. The transporter according to claim 7, wherein the optical receiver comprises a microscope.

9. The transporter according to any previous claim, wherein the carriers are Petri dishes, multi-well plates or any other device containing biological specimens.

15

10. A method of transporting specimen carriers to a processing position, comprising the steps of:

providing a vertical input magazine and an output magazine of carriers, one above the other;

20

singling out a carrier from the input magazine and moving it vertically to an intermediate position which is located between the input and output magazines and halting it there; and
moving the carrier to an output location where it is transferred to the output magazine.

25

11. The method according to claim 10, further comprising moving the carrier incrementally up or down at the intermediate position using the singulator.

12. The method according to claim 10 or 11, further comprising the steps of:
moving a processing tool horizontally to a position above and/or below the carrier at the intermediate position; and
withdrawing the processing tool after carrying out processing.

30

13. The method according to any of claims 10 to 12, wherein the movement of the

carrier to the intermediate position is independent of movements of the carriers in the input and output magazines

14. The method according to claim 12 or 13, wherein the processing tool is an optical receiver.

5

Abstract

The present application a transporter (100) for transporting specimen carriers (8) to a processing station (40), comprising a first vertical input magazine (1) of carriers (8), a
5 second vertical output magazine (6) of carriers, and a singulator (3) located between the first and second magazines (1,6). The first and second magazines (1,6) may be located one above the other. Preferably, the first and second magazines (1,6) and the singulator (3) are vertically aligned so that a carrier (8) follows a straight vertical path. This provides a compact arrangement which takes up the minimum of floor space in the
10 laboratory. The singulator (3) receives carriers (8) one-at-a-time from the input magazine (1) and moves them vertically to a processing position (40). After processing, the singulator (3) then delivers each carrier to an output location where it is transferred to the output magazine (6). The singulator (3) may move a carrier (8) upwards or downwards at the processing position (40) independent of any movement of the carriers
15 (8) in the input and/or output magazines (1,6). The drives for the input and output magazine (1,6) are preferably simple gravity drives but the present invention is not limited thereto. The drive (10) for the singulator is preferably a stepping motor or DC servo-motor.

20 Fig. 1

1/3




Fig. 1




Fig. 3







Fig. 2



Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

OR

☒ Registered practitioner(s) name/registration number listed below

Place Customer
Number Bar Code
Label here

Name	Registration Number	Name	Registration Number
Michael Stark	32,495	Myra McCormack	36,602
Steven P. Berman	24,772	Ellen C. Coletti	34,140
Andrea L. Colby	30,194	Mary A. Appollina	34,087

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number or Bar Code Label

OR ☒ Correspondence address below

Name	Philip S. Johnson		
Address	Johnson & Johnson		
Address	One Johnson & Johnson Plaza		
City	New Brunswick	State	NJ
ZIP	08933-7003		
Country	USA	Telephone	(732) 524-2359
Fax	(732) 524-2808		

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any))		Family Name or Surname	
Roger François Gabrielle Armand		Nuyens	
Inventor's Signature	Date		Sept. 9 2001
Residence: City	2460 Kasterlee	State	Belgium
Post Office Address	Janssen Pharmaceutica N.V., Turnhoutseweg 30		
Post Office Address			
City	Beerse	State	Belgium
ZIP	2340	Country	Belgium

☐ Additional inventors are being named on the supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)	Attorney Docket Number	JAB 1513-PCT-USA
	First Named Inventor	NUYENS, Roger F. G. A.
	COMPLETE IF KNOWN	
	Application Number	/
	Filing Date	
	Group Art Unit	
<input checked="" type="checkbox"/> Declaration Submitted with Initial Filing	OR	<input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)
Examiner Name		

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**APPARATUS FOR TRANSPORTING CARRIERS TO A PROCESSING STATION
AND METHOD OF OPERATING THE SAM**

the specification of which

☐ is attached hereto
OR

☒ was filed on (MM/DD/YYYY) 07/03/2000 / as United States Application Number or PCT International

Application Number PCT/EP00/062451 and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
99202173.3 ✓	EP ✓	07/03/1999 ✓	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.